

# RigidTile<sup>™</sup> **FIRM** Premier



## THE SMART ADVANTAGE SPC

PROFESSIONAL



CAPRI RT-FMP747

**TORLYS**  
smart floors

[torlys.com](http://torlys.com)

### Visuals, Value & Performance.

RigidTile<sup>™</sup> Firm is a 5-layer continuous press construction that offers all of the benefits of a TORLYS Smart Floors in an SPC Vinyl. RigidTile<sup>™</sup> Firm Premier has 5 designs in beautiful matte finishes; a perfect alternative to porcelain or stone tile.

# TORLYS Smart Advantage



## WATERPROOF FLOORING

RigidTile™ is 100% waterproof – exclusively backed by TORLYS Flood Warranty.



## TORLYS FLOOD WARRANTY

RigidTile™ is protected from water damage to the floors caused by floods.



## TORLYS BULLDOG™ EASY PLANK REPLACER

Enables single planks of RigidTile™ to be replaced, quickly and easily. No mess, no dust, no downtime.



## FOAMPLUS™ BLUE WITH MICROBAN®

Superior sound reduction and shock-absorption with anti-crush technology. Infused with Microban® technology during the manufacturing process for proven 24/7 defense against mold and odor causing bacteria.



## MAXX FINISH WITH MICROBAN®

An exclusive long lasting finish with nano technology utilizing aluminum oxide that provides superior stain and scratch resistance. Built-in 24/7 protection against stain and odor causing bacteria for a 99% cleaner floor.







# Premier



**3/16" x 12" x 24" (nominal)**

**22 mil wear layer**

**5mm (1mm IXPE) x 303.1mm x 607.2mm**


**0.55mm wear layer**

- Perfect flooring for all seasonal spaces including cottages and sunrooms.\*
  - Remarkable dimension stability that will withstand temperature swings from -4°F to 122°F (-20°C to 50°C).
  - No peaking, no gapping and no cupping – guaranteed!
  - Install directly over other hard surfaces with minimal subfloor preparation.
  - Transition Free up to 70'x70' (21m x 21m) and can be fixed/floated on the same floor.\*
- Realistic grout lines color coordinated to the stunning tile patterns.
- TORLYS FoamPlus™ Blue attached underlay has built-in 24/7 protection against mold and odor causing bacteria, extending the lifetime of the floor.
- Complete with TORLYS Maxx Finish featuring 24/7 protection against stain and odor causing bacteria for a 99% cleaner floor.

*\*Please refer to installation instructions for complete details.*

A rectangular tile sample with a uniform, medium-grey color and a subtle, fine-grained texture.


METRO GREY RT-FMP745

A rectangular tile sample with a dark brown, almost black, color and a heavily textured, stone-like appearance with some lighter brown veining.

AMHERST RT-FMP746

A rectangular tile sample with a light grey to off-white color and a smooth, slightly glossy finish with some very subtle variations in tone.

CAPRI RT-FMP747

A rectangular tile sample with a warm, light beige or tan color and a smooth, slightly glossy finish with some subtle variations in tone.

MODENA RT-FMP748

A rectangular tile sample with a dark, almost black, color and a highly textured, veined appearance with prominent white and light grey veins running through it.

NERO RT-FMP749

# ASTM and ANSI Product Performance Tests

Standard	Description	Test Result	Notes
ASTM E648-17	Critical Radiant Flux	Average Critical Radiant Flux: $\geq 0.45 \text{ W/cm}^2$	NFPA Life Safety Code 101 Classification: Class 1
ASTM E662-17a	Smoke Density	$\leq 450$	Passes $\leq 450$ Criteria, as per NFPA Life Safety Code 101
Phthalates, as per CPSC-CH-C1001-09.3 (California Proposition 65)	Phthalates	Does not contain phthalate esters	
RoSH	Heavy Metals	Pass	
ASTM D5116-10 (Small Chamber)	Formaldehyde Emissions	No Formaldehyde	
ANSI A137.1-2012 (aka DCOF AcuTest)	Coefficient of Friction (Floor Slip Resistance): a) Dynamic Coefficient of Friction(wet) Coefficient of Friction (Floor Slip Resistance): b) Static Coefficient of Friction (dry)	Mean Result: 0.44  Mean Result: 0.49	Passes the $\geq 0.42$ requirement
ASTM F925	Resistance to Chemicals	Slight Surface Change / Dulling by White Mineral Oil and NaOH Solution	The scale is 0-3; 0 = no change; 1 = slight change; 2 = moderate change; 3 = severe change
ASTM F1515	Resistance to Light	$\Delta E \leq 8$	Test result after 400 hours exposure
ASTM E492-09 (2016) - ASTM E989-06 (2012)	Impact Insulation Class	IIC up to 73	Contact TORLYS for details.
ASTM E90-09 (2016) / ASTM E413 - 16	Sound Transmission Coefficient	STC 61	

## Warranties

**25-Year Homeowner Limited Warranty** for Wear, Stain, and Water; and a Lifetime Structural and Joint Integrity/No Gapping Warranty.

**10-Year Limited Commercial, Wear, Structural and Joint Integrity/No Gapping Warranty.**

**Flood Warranty:** RigidTile™ Firm Premier is covered by an exclusive Flood warranty. Fully waterproof when installed with a perimeter seal. Visit [torlys.com](http://torlys.com) for full warranty and installation information.



**TORLYS**  
smart floors

[torlys.com](http://torlys.com)

September 2020