

# RigidWood<sup>TM</sup> Vista Plus



THE SMART ADVANTAGE LVT

PROFESSIONAL



HELM OAK RW-VP154

The Seal of Science.



The Art of Flooring.

**TORLYS**  
smart floors

[torlys.com](http://torlys.com)

## The Perfect Rigid LVT Floor.

RigidWood<sup>TM</sup> Vista Plus has all the performance benefits of a TORLYS smart floor...now in Rigid LVT. The Flexibility you want. The Rigidity you need. Only RigidWood<sup>TM</sup> Vista Plus offers a quiet, solid-feeling floor with no peaking, gapping, or cupping.

## TORLYS Exclusives



### TORLYS BULLDOG™ EASY PLANK REPLACER

#### "Your Floor's Best Friend"

The Bulldog allows you to:

- Fix major mishaps quickly and easily.
- Replace a damaged plank, not your entire floor.

TORLYS dealers can easily replace damaged or dented pieces. No glue. No nails.



### UNICLIC® JOINT TECHNOLOGY

For remarkably stable, gap resistant floors. Side and end joints have patented Uniclic® joint technology, and floors are backed by a gap warranty.



### TORLYS FOAMPLUS™ BLUE UNDERLAY

For superior sound reduction, shock absorption, moisture protection with built-in Microban® antimicrobial product protection and anti-crush for long-lasting performance.



### TORLYS FLOOD WARRANTY

RigidWood™ is protected from water damage caused by floods with TORLYS Flood Warranty.



Ultra-Stable



Waterproof



Gap  
Resistant



Warm &  
Quiet



Ease of  
Repair



Peace-  
of-Mind  
Durability



Easy to  
Maintain



Dent  
Resistant



Clean and  
Healthy



Pet  
Friendly

# RigidWood™

## Vista Plus



### Striking wood styles in 6" wide planks.

RigidWood™ Vista Plus has the Smart Advantage of TORLYS high-quality, innovative construction. The new formulation is a unique 7-layer process that includes an ultra-durable scratch resistant finish and patented Uniclic® joint. The result is an optimal blend of flexibility and rigidity.

5/32" (T) x 6" (W) x 47-3/4" (L) (nominal)  
4.5mm (T) x 150m (W) x 1211mm (L)

- Beautiful deep textured surfaces
- Conforms to subfloor for a quieter, more solid feel
- Creates remarkable dimensional stability – peak/gap free\* – withstands 80°C temperature swings from -30°C - +50°C (-22°F to +122°F)
- No transitions in 80' x 80' spaces\*
- Matching painted bevels
- Can be fixed and floated on same floor
- More dent resistant than traditional LVT
- Superior scratch and stain resistance
- 0.3mm (12 mils) wear layer
- TORLYS FoamPlus™ Blue Underlay included with Microban® antibacterial protection built in
- Suitable to install over radiant heat
- Matching flush stair nosing available

*\*Check installation instructions and warranty for details.*

FOREMAST RW-VP150

SPINNAKER RW-VP151

DECK OAK RW-VP152

BLUEPETER RW-VP153

HELM OAK RW-VP154

## ASTM and ANSI Product Performance Tests

Standard	Description	Test Result	Notes
ASTM E648-17	Critical Radiant Flux	Average Critical Radiant Flux: $\geq 0.45 \text{ W/cm}^2$	NFPA Life Safety Code 101 Classification: Class 1
ASTM E662-17a	Smoke Density	$\leq 450$	Passes $\leq 450$ Criteria, as per NFPA Life Safety Code 101
Phthalates, as per CPSC-CH-C1001-09.3 (California Proposition 65)	Phthalates	Does not contain phthalate esters	
ASTM D5116-10 (Small Chamber)	Formaldehyde Emissions	No Formaldehyde	
ANSI A137.1-2012 (aka DCOF AcuTest) Replaces ASTM C1028-07*	Coefficient of Friction (Floor Slip Resistance): a) Dynamic Coefficient of Friction(wet) Coefficient of Friction (Floor Slip Resistance): b) Static Coefficient of Friction (dry)	Mean Result: 0.44  Mean Result: 0.49	Passes the $\geq 0.42$ requirement
ASTM F925	Resistance to Chemicals	Slight Surface Change / Dulling by White Mineral Oil and NaOH Solution	The scale is 0-3; 0 = no change; 1 = slight change; 2 = moderate change; 3 = severe change
ASTM F1515	Resistance to Light	$\Delta E \leq 8$	Test result after 400 hours exposure
ASTM E492-09 (2016) - ASTM E989-06 (2012)	Impact Insulation Class	IIC 70	Testing on 8" concrete slab, with suspended ceiling
ASTM E90-09 (2016) / ASTM E413 - 16	Sound Transmission Coefficient	STC 61	

\* Note: "Obsolete, misleading test withdrawn by ASTM in 2014. Not valid for assessing pedestrian safety." <http://www.astm.org/Standards/C1028.htm>

## Warranties

**20-Year Homeowner Limited Warranty** for Wear, Stain, and Water; and a Lifetime Structural and Joint Integrity/No Gapping Warranty.

**5-Year Limited Commercial**, Wear, Structural and Joint Integrity/No Gapping Warranty.

**Flood Warranty:** RigidWood™ Vista Plus is covered by an exclusive Flood warranty. Fully waterproof when installed with a perimeter seal. Visit [torlys.com](http://torlys.com) for full warranty and installation information.



**TORLYS**  
**FoamPlus Blue**  
with MICROBAN®



**UNICLIC**®



**TORLYS**  
smart floors

[torlys.com](http://torlys.com)

MK-BL-RW906